

Technical University of Denmark



Satellite altimetry-derived water level for calibration of river morphological parameters in hydrodynamic models

Jiang, Liguang; Madsen, Henrik; Bauer-Gottwein, Peter

Published in:
Geophysical Research Abstracts

Publication date:
2018

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Jiang, L., Madsen, H., & Bauer-Gottwein, P. (2018). Satellite altimetry-derived water level for calibration of river morphological parameters in hydrodynamic models. Geophysical Research Abstracts, 20, [EGU2018-12562-1].

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



Satellite altimetry-derived water level for calibration of river morphological parameters in hydrodynamic models

Liguang Jiang (1), Henrik Madsen (2), and Peter Bauer-Gottwein (1)

(1) Department of Environmental Engineering, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark (ljia@env.dtu.dk; pbau@env.dtu.dk), (2) DHI, Agern Allé 5, 2970 Hørsholm, Denmark (hem@dhigroup.com)

Hydrodynamic (HD) modeling has become an essential tool for understanding and predicting hydrologic processes and has been an important research topic in hydrological science. HD models can simulate details of river flow that rainfall-runoff models alone cannot elucidate, such as the water depth, inundation extent, distributed water-surface elevation (WSE), and timing of peak flows. Therefore, HD modeling is of paramount importance in flood forecasting and management systems.

One of the key steps in HD modeling is calibration where model parameters are adjusted to minimize the difference between modeled and measured quantities. Model calibration has conventionally relied on surveyed bathymetric data. However, river bathymetry data is not available in most parts of the world. This impedes river modeling and operational flood forecasting for poorly monitored basins.

Advances in remote sensing observations have played an increasingly prominent role in hydrologic and hydraulic fields, and have promoted the estimates of key hydrologic and hydraulic variables (e.g., snow depth, WSE, river geometry, discharge, and storage, etc.). WSE derived from satellite altimetry is complementary to gauge data, especially in data-sparse and ungauged regions. Moreover, satellite altimetry provides spatially-distributed WSE, which is valuable for calibration of models with distributed, non-uniform parameters.

This work investigates the added value of a constellation of altimetry missions for calibrating a 1D HD model (MIKE Hydro River) and explores parameter sensitivity of altimetry-derived SWE. To this end, a series of calibration experiments are carried out using synthetic and real-world data from multiple missions (Envisat/SARAL, Jason-1/2, CryoSat-2) over the Songhua River basin. In this wide-channel river model, spatially variable Manning's roughness coefficient (n) and river bed elevation (Z_0) are considered for 23 cross sections. The synthetic experiments show that the spatial variability of n and Z_0 can be well constrained by CryoSat-2, and to a lesser extent by Envisat and SARAL with regularized inversion method. However, Jason-1/2 alone cannot constrain these parameters due to the coarse spatial sampling pattern. We find that higher accuracy of altimetry-derived WSE does not proportionally decrease parameter uncertainty for all cross sections. Instead, increased spatial sampling density helps to capture the spatial variability of morphological parameters. We conclude that increased spatial sampling density is more important than temporal sampling density and data accuracy for calibrating morphological parameters of large-scale river models.